

# **HEM**PAVING

**SIMPLY GREAT SOLUTIONS**

## **3 - Wheel Concrete Breaker**



HEAVY EQUIPMENT MFG • 601 E FIRST ST • GRUNDY CENTER, IA 50638 U.S.A.  
[www.hempaving.com](http://www.hempaving.com) +1-319-824-3011 [info@hempaving.com](mailto:info@hempaving.com)



# 3-Wheel Concrete Breaker

## Standard Spec Sheet

**Honda Gas Engine 20 hp**

**Two-Way Stroke Adjustment**

*Maximum: 30"*

*Variable Stroke: 7-23"*

**Cycle Rate**

*Maximum Drop: 28 blows per min.*

*Partial Drop: 35-60 blows per min*

**Indexing Control**

*0-36" (Infinitely variable)*

**Frame**

*One-piece, unitized frame and tower with removable front axle*

**Hydraulic System**

*Gear Pump: 6 gpm @ 1300 psi with 20 gal hydraulic reservoir*

*Cylinder: 2" bore with load-rated cushioning*

*Wheel Motor: low-speed, high-torque with double, counter balanced valves for positive control and braking*

**Tires**

*Rim width: 6"*

*Tire Type: pneumatic, tubeless, 4 ply*

*Tire Size: 20.5" x 8" x 10"*

**Wiring**

*Electrical control circuitry integrally counted inside low-vibration enclosures*

**Custom Trailer**

**Dimensions**

*Height: 89"*

*Length: 87" (with handle in storage position)*

*105" (with handle in operate position)*

*Width: 44" (outriggers up)*

*Shipping Weight: 2580 lbs.*

*Breaking Weight: 1080 lbs.*



**Authorized Dealer:**

[www.hempaving.com](http://www.hempaving.com)

+1-319-824-3011

[info@hempaving.com](mailto:info@hempaving.com)